




Rigid Coupling



Nominal size mm/in	Pipe O.D mm/in	Working Pressure MPa/psi	Dimension mm			Bolt/Nut
			A	B	C	
25	33.7	2.07	98	58	45	M10*50
1	1.315	300				
32	42.4	2.07	106	68	45	M10*50
1 1/4	1.66	300				
40	48.3	2.07	112	73	45	M10*50
1 1/2	1.9	300				
50	60.3	2.07	128	86	45	M10*55
2	2.375	300				
65	73	2.07	138	96	45	M10*55
2 1/2	2.875	300				
65	76.1	2.07	139	99	45	M10*55
2 1/2	3	300				
80	88.9	2.07	158	112	45	M10*60
3	3.5	300				
100	114.3	2.07	192	143	50	2-M12*70
4	4.5	300				
125	139.7	2.07	223	169	50	2-M12*75
5	5.5	300				
125	141.3	2.07	223	169	50	2-M12*75
5	5.563	300				
150	165.1	2.07	252	198	50	2-M12*75
6	6.5	300				
150	168.3	2.07	252	200	50	2-M12*75
6	6.625	300				
200	216.3	2.07	326	252	60	2-M16*90
8	8.516	300				
200	219.1	2.07	322	254	58	2-M16*90
8	8.625	300				
250	267.4	2.07	384	309	62	2-M20*100
10	10.528	300				
250	273	2.07	388	314	62	2-M20*110
10	10.75	300				
300	318.5	2.07	440	362	62	2-M20*110
12	12.539	300				
300	323.9	2.07	443	365	62	2-M20*110
12	12.75	300				
350	355.6	2.07	510	415	72	3-M22*140
14	14.000	300				
350	377.0	2.07	535	435	72	3-M22*140
14	14.850	300				
400	406.4	2.07	575	468	72	3-M22*140
16	16.000	300				
400	426.0	1.60	592	490	72	3-M22*140
16	16.770	225				
450	457.2	1.60	608	508	78	3-M22*140
18	18.000	225				
450	480.0	1.60	630	533	78	3-M22*140
18	18.898	225				
500	508.0	1.60	660	563	78	4-M22*140
20	20.000	225				
500	530.0	1.60	700	595	78	4-M22*140
20	20.866	225				
600	609.6	1.60	772	668	78	4-M24*140
24	24.000	225				
600	630	1.60	796	692	78	4-M24*140
24	24.80	225				